

Fig no. V-Z05TC Tube Bore
1/2" - 4" DN15 ~ DN100



Features:

Investment casting body
Blow-out-proof stem
In-line Maintenance
For Hygienic application

Standard Compliance :


Body wall thickness : ASTM B16.34
Clamp end : 3A
Face to face : MD's standard
Body material : ASTM A351
Pressure testing : EN 12266/ API 598

Specification :

End Connection : Clamp end
Working pressure : 1000 psi (PN 63) for DN8- DN 50
800 psi (PN40) for DN 65-DN100
Temperature : -20 ~ 160°C
Inter finish-polished to SV1

Options:

1. Non cavity filler seat



MATERIALS LIST

NO.	PART NAME	MATERIAL
1	BODY	ASTM A351 Gr.CF8M
4	BALL	ASTM A351 Gr.CF8M
5	STEM	SS316
9	END CAP	ASTM A351 Gr.CF8M
11	BODY SEAL	PTFE.
12	SEAT	PTFE.
13	THRUST WASHER	PTFE.
14	STEM PACKING	PTFE.
15	GLAND	SS304
19	HANDLE	SS304
21	HANDLE COVER	PLASTIC
23	HANDLE WASHER	SS304
24	HANDLE NUT	SS304
35	BODY BOLT	SS304
36	BOLT WASHER	SS304
37	BOLT NUT	SS304

DIMENSIONS

unit:mm

SIZE	PORT	L	E	H	ØD
DN15 1/2"	9.5	89.0	106.0	52.0	25.4
DN20 3/4"	15.9	101.0	106.0	55.0	25.4
DN25 1"	22.2	114.0	135.0	70.0	50.4
DN40 1-1/2"	35.0	140.0	182.0	89.0	50.4
DN50 2"	47.6	156.0	182.0	97.0	63.6
DN65 2-1/2"	60.2	197.0	263.0	140.0	77.5
DN80 3"	73.0	229.0	263.0	152.0	90.8
DN100 4"	97.4	241.0	285.0	184.0	118.5

