

Fig no. K-302L/T Standard Bore
1/4" - 2" DN 8- DN 50



Features :

Investment Casting
Blow out proof stem
360 degree rotation design
For Chemical, Industrial Application
Carbon Steel or Super Alloy upon request

Standard Compliance :

Body wall thickness : EN 12516-1/3
Threaded end : BS 21 (BSP)
BSPT
ISO 228-1G
DIN 2999
ISO 7-1Rp




Face to Face : MD's standard
Body material : EN1503-1
Pressure testing : EN 12266

Specification :

End connection : Threaded end
Working Pressure : 63 bar (CWP)
Temperature : -20 to 180°C

MATERIAL LIST

NO.	PART NAME	MATERIAL
1	BODY	1.4408/EN1503-1
4	BALL	ASTM A351 Gr.CF8M
5	STEM	SS316
9	END CAP	1.4408/EN1503-1
11	BODY SEAL	PTFE.
12	SEAT	PTFE.
13	THRUST WASHER	PTFE.
14	STEM PACKING	PTFE.
16	GLAND NUT	SS304
19	HANDLE	SS304
21	HANDLE COVER	PLASTIC
23	HANDLE WASHER	SS304
24	HANDLE NUT	SS304
28	LOCKING PAD	SS304



DIMENSION

SIZE		unit:mm									
DN	PORT	L	L5	E	H	M	P1	P2			
DN8	1/4"	11.0	69.4	35.0	106.0	61.0	10-24UNC	13.0	28.5		
DN10	3/8"	11.0	69.4	35.0	106.0	61.0	10-24UNC	13.0	28.5		
DN15	1/2"	12.7	76.0	37.5	138.0	65.5	10-24UNC	13.0	28.5		
DN20	3/4"	16.0	86.6	45.0	138.0	71.0	10-24UNC	21.0	34.6		
DN25	1"	20.0	102.0	51.0	157.0	76.0	10-24UNC	21.0	34.6		
DN32	1-1/4"	25.0	118.0	58.0	157.0	81.5	10-24UNC	24.0	38.0		
DN40	1-1/2"	32.0	126.0	63.0	220.0	102.0	1/4"-20UNC	24.0	38.0		
DN50	2"	38.1	149.0	77.0	220.0	112.2	1/4"-20UNC	24.0	38.0		