One Piece Flanged Fire Safe Approved Ball Valve, Reduced Bore, ANSI#150

MODENTIC

Fig No. MD-51FS **Reduced Bore**
3/4" - 6" **DN 20 ~ DN 150**

Features :

API 607 4th Fire Safe Approved
Investment casting componment
Blow out proof design, Anti-static device
ISO 5211 Mounting flange
For General chemical and industrial application
Carbon Steel or Super Alloy available upon request

Standard Compliance :

Body wall thickness : B16.34
Face to face length : ANSI B16.10 Class 150
Flange dimension : ANSI B 16.5 Class 150
Finish : 125-250 AARH
Body Material : ASTM A351
Pressure testing : EN 12266

Specification :

End connection : Flanged RF end
Working pressure : 275 psi (CWP)
Temperature : -20 ~ 180°C

MATERIALS LIST

NO.	PART NAME	MATERIAL
1	BODY	ASTM A351 Gr.CF8M
4	BALL	ASTM A351 Gr.CF8M
5	STEM	SS316
9	INSERT	ASTM A351 Gr.CF8M
11	BODY SEAL	GRAPHITE
12	SEAT	RPTFE.
13	THRUST WASHER	GRAPHITE
13-1	THRUST WASHER	PTFE.
14	STEM PACKING	GRAPHITE
15	GLAND	ASTM A351 Gr.CF8
19	HANDLE	FCD45
28	STOP PLATE	SS304
32	PACKING FOLLWER	PTFE.
41	SNAP RING	SS304
42	GLAND BOLT	SS304
56	BEARING	PTFE.





DIMENSIONS

unit:mm

SIZE		PORT	L	E	H	ØG	ØJ	ØI	T	F	M	ØN	ØK	ØD
DN20	3/4"	16.0	115.0	129.5	70.5	98.0	70.0	43.0	12.7	2.0	4	16.0	36.0	20.0
DN25	1"	20.0	127.0	130.8	80.2	108.0	79.5	51.0	12.0	2.0	4	16.0	42.0	25.0
DN40	1-1/2"	32.5	165.0	163.0	99.0	127.0	98.5	73.0	14.8	2.0	4	16.0	50.0	38.0
DN50	2"	38.0	178.0	202.0	130.4	152.0	120.5	97.0	16.5	2.0	4	19.0	70.0	46.0
DN65	2-1/2"	50.0	190.0	202.0	137.9	178.0	139.5	105.0	18.0	2.0	4	19.0	70.0	65.0
DN80	3"	58.0	203.0	323.5	159.3	190.0	152.5	127.0	19.5	2.0	4	19.0	102.0	78.0
DN100	4"	80.0	229.0	323.5	182.3	229.0	190.5	163.0	24.3	2.0	8	19.0	102.0	95.0
DN150	6"	115.0	267.0	752.5	241.6	279.0	241.5	216.0	25.4	2.0	8	22.0	125.0	150.0