


Fig No. MD-52FS Full Bore
1/2" - 6" DN 15 ~ DN 150



MATERIALS LIST

NO.	PART NAME	MATERIAL
1	BODY	ASTM A351 Gr. CN7M
4	BALL	ASTM A351 Gr. CN7M
5	STEM	ASTM A351 Gr. CN7M
9	END CAP	ASTM A351 Gr. CN7M
11	BODY SEAL	316/GRAPHITE
12	SEAT	RPTFE.
13	THRUST WASHER	GRAPHITE
13-1	THRUST WASHER	PTFE.
14	STEM PACKING	GRAPHITE
15	GLAND	ASTM A351 Gr.CF8
19	HANDLE	FCD45
28	STOP PLATE	SS304
32	PACKING FOLLWER	PTFE.
35	STUD	SS304
37	BOLT NUT	SS304
41	SNAP RING	SS304
42	GLAND BOLT	SS304
56	BEARING	PTFE.



Features :


API 607 4th Fire Safe Approved
Investment casting component
Blow out proof design
ISO 5211 Mounting flange
For General chemical and industrial application

Standard Compliance :

Body wall thickness : B16.34
Face to face length : ANSI B16.10 Class 150
Flange dimension : ANSI B 16.5 Class 150
Finish : 125-250 AARH
Body Material : ASTM A351
Pressure testing : EN 12266

Specification :

End connection : Flanged RF end
Working pressure : 230 psi (CWP)
Temperature : -20 ~ 180°C



DIMENSIONS

DIMENSIONS												unit:mm	
SIZE	PORT	L	E	H	ØG	ØJ	ØI	T	F	M	ØN	ØK	
DN15	1/2"	15.0	108.0	130.8	77.7	89.0	60.5	35.0	11.6	2.0	4	16.0	42.0
DN20	3/4"	20.0	117.0	130.8	80.2	98.0	70.0	43.0	11.6	2.0	4	16.0	42.0
DN25	1"	25.4	127.0	163.0	92.1	108.0	79.5	51.0	12.0	2.0	4	16.0	50.0
DN32	1-1/4"	32.0	140.0	163.0	96.8	117.5	88.5	63.5	13.3	2.0	4	16.0	50.0
DN40	1-1/2"	38.0	165.0	202.0	130.4	127.0	98.5	73.0	15.2	2.0	4	16.0	70.0
DN50	2"	50.0	178.0	202.0	137.9	152.0	120.5	92.0	16.3	2.0	4	19.0	70.0
DN65	2-1/2"	63.0	190.0	202.0	160.5	178.0	139.5	105.0	18.0	2.0	4	19.0	70.0
DN80	3"	80.0	203.0	323.5	174.7	190.5	152.5	127.0	19.5	2.0	4	19.0	102.0
DN100	4"	98.0	229.0	323.5	197.0	229.0	190.5	157.0	24.3	2.0	8	19.0	102.0
DN125	5"	125.0	356.0	752.5	249.0	254.0	216.0	186.0	24.5	2.0	8	22.0	125.0
DN150	6"	152.0	394.0	752.5	267.5	279.0	241.5	216.0	25.8	2.0	8	22.0	125.0